

Clean smooth finish brightens up any buildings interior! Class A fire rating provides peace of mind! Available with E-Z Seal Tab for quick installation!



Benefits of Low-E Class A White Insulation:

- Clean White Surface
- Available with E-Z Seal Tab
 - Excellent vapor barrier
- Installs easily with razor knife and white foil tape
 - Class A/Class 1 Fire Rating
 - Superior thermal performance
 - Improves insulation systems performance
 - Insect/bird resistant
 - Seals tight around fasteners
 - Certified astm testing





Environmentally Safe Products Inc. 313 West Golden Ln. New Oxford, PA 17350 Phone: 800-289-5693 Fax: (717)-624-7089 E-Mail sales@low-e.com Web: www.low-e.com

Low-E Class A WhiteTM Product Information

<u>Product Identification:</u>	
Product Name:	Low-E Class A White™ Insulation
Product Codes:	E4FC0, E6FC0, E40C0, E40CS, E60C0, E60CS
Other Information:	
Finished Dimension:	Available in standard length rolls 48" Width x 125' Length, 72" Width x 75' Length (Shipped in roll form)
Styles:	Available in E-Z Seal, Staple Flange or Trimmed Edge
Core Material:	Polyethylene
Facing:	99.4% Polished Aluminum non reinforced/ White Aluminum
Perm Rating:	WVTR: 0.008
Flame and Smoke:	ASTM E-84-98 Flame Spread: 10 Smoke Developed: 15
R-Value:	ASTM C-976: Down 8.33
	ASTM C-976: Horizontal 7.00
	ASTM C-976: Up 6.14
Emittance:	0.03 (foil side)

Notes and Warnings:

Warning: Although ESP Low-E® Insulation Products are all ASTM fire tested and have excellent fire ratings; it is recommended that they or any insulation material should not be exposed to open flame or other ignition sources of sufficient intensity during shipment, storage or installation.

Caution: Aluminum is an Electrical Conductor. Please use caution when working around electrical sources including overhead power lines.





^{*}System R-Values as per ASTM C-976, air to air

^{*}Adjusted to meet criteria equivalent to ASTM 1224